

Firefly[®]₃



SOLAS Rescue Strobe Light

Product No. 3995.3 (Carded)

Product No. 3995.4 (Bulk)

- > Large sliding switch easy to operate with gloved hands
- > Newly-designed base platform allows unit to stand upright for hands-free operation
- > 1" webbing slots provide secure anchor points
- > 360° high intensity Xenon strobe visible for up to 2 miles
- > Ideal for life vests, safety harnesses, float coats, work suits, immersion suits, backpacks, flight suits



Size:	4.75 x 2.2 x 1.2 in. (12.1 x 5.6 x 3 cm)
Weight:	3.8 oz (105 g) with lithium batteries
Material:	Polycarbonate
Color:	International Orange
Operation:	Slide switch up to "ON" position
Waterproof:	Factory tested to 10 meters (33 ft)
Beam Angle:	.75 cd minimum (3.5 cd maximum) in all directions of upper hemisphere
Visibility:	*Minimum 1 mile (.87 NM); Maximum 2 miles (1.74 NM); may increase at higher altitudes or dry conditions
Flash Rate:	60± 10/minute, nominal
Lamp:	High intensity Xenon strobe
Battery Type:	2 "AA" alkaline or 1.5V lithium (not included) SOLAS Approval with lithium batteries only
Certification:	USCG 161.012/58/0 (alkaline or lithium) USCG SOLAS 161.112/58/0; IMO LSA Code Res. MSC. 81(70); FAA TSOC 85 approved (with lithium dated batteries only)
Limited Warranty:	1 year
Operational Life:	Minimum of 8 hours continuous @ -1°C meets USCG and IMO (SOLAS) specifications
Carton Dimensions:	Carded - 6.5 x 5.0 x 11.0 in. (16.5 x 12.7 x 28 cm)
Units per Carton:	Carded - 6
Carton Weight:	1.9 lbs (.9 kg)



ACR Electronics, Inc.
5757 Ravenswood Road
Fort Lauderdale, FL 33312, U.S.A.
Tel Worldwide: +1(954) 981-3333
Fax: +1(954) 983-5087
www.acrelectronics.com

*USCG Minimum luminous intensity of light